





When secure IDs are a priority, choose Zebra's rugged P640i dual-sided laminating printer. This industry-leading security printer has high output speed and one of the lowest consumables cost per card in its class. Designed for reliable, continuous operation in demanding production environments, the Zebra P640i delivers dual sided-printing and dual-sided lamination with high throughput and great print quality, making it the right choice for printing more secure, more durable ID cards.

# **High Productivity with Unique Cost Saving Features**

- » Consistent, reliable operation with high print speed and continuous card loading for maximum throughput
- » Among the lowest consumables cost per card of any printer in its class.
- » Wasteless lamination reduces impact on the environment

### Easy-to-Use

- » Plug and play USB or Ethernet interface simplifies set-up
- » Automatic color optimization and driver configuration
- » Weight saving design makes the P640i easier to transport
- » Translucent covers allow you to see when supplies are running low. Blank cards can be added while printing for convenience and time savings

# **Encoding and Network Expansion Options**

- » 3 track magnetic stripe encoding
- » Contact and contactless smart card encoding capabilities
- » Optional built-in 10/100 Ethernet for printer networking simplifies device management and enables distributed printing across sites

# Industry Leading Security & Performance Features

- » Complete system security features & options for printer, ribbons, laminate, cards, and card issuance process
- » Unique card transport with stable card movement across printhead for superior print quality
- » Enhanced ribbon formulation for optimal color output
- » Ribbon image counter and ribbon low notification

#### Ideal for:

- » Drivers Licenses
- » Government & Military ID Cards
- » High Security Access Control ID Cards
- » Law Enforcement and Correctional Facility ID Cards
- » Airport ID Cards
- » Applications requiring long lasting, secure issuance of tamper-evident ID's

# P640i

# **Card Printer Product Specifications**



# **General Specifications**

- » Dual-sided color printing
- » One-pass waste-free dual-sided lamination
- » Micro-positioning card transport system for enhanced color photos
- » Covert printing capability text approx 17 mil high
- » Automated card cleaning before printing
- » Windows® drivers for 2000 and XP with advanced security features (ID/Log & password protection)
- » One year printer warranty
- » One year (unlimited passes) printhead warranty

### **Printing**

- » Color dye sublimation and resin K
- » 120 cards per hour dual-sided printing and laminating (YMCK ribbon & 1.0 mil laminate both sides)
- » 300 dpi (11.8 dots/mm) print resolution

#### **Bar Codes**

» Bar codes and other symbologies available via Windows driver

» True Type or other type fonts via Windows driver

## **Card Specifications\***

- » Types: PVC Composite
- » Card width/length: ISO CR-80 ISO 7810 2.12" (54mm) x 3.38" (86mm)
- » HiCo Magnetic Stripe ISO 7811
- » Smart Card contact and contactless
- » Card thickness: 27 mil 33 mil
- » Card input hopper capacity: 150 cards

### **Ribbon Specifications\***

- » YMCK: 600 cards/roll
- » YMCKK: 500 cards/roll
- » YMCUvK: 500 cards/roll
- » Cleaning cartridge: cleans 3,000+ cards



\*for optimum printer performance use Genuine Zebra Supplies

# **Laminate Specifications\*\***

- » Linerless & wastefree 1.0 mil laminate, 600 cards/roll
- » 2 Laminate cassettes (upper & lower)
- » Laminates available:

Clear full size, clear for magnetic stripe cards and clear for smart cards. Custom laminates available upon request:

Holographic images

Special OVD images

UV images

\*\*for optimum laminator performance use Genuine Zebra Supplies.

#### **Communications Interface**

- » USB 1.1 (Standard, USB 2.0 compatible)
- » Factory Installed Options

Built-In 10/100 Ethernet

Bi-directional Parallel with ECP support

### **Mechanical**

- » Width: 27.5 in (699 mm) not including exit hopper
- » Depth: 9.7 in (246 mm)
- » Height: 11.5 in (292 mm)
- » Weight: 35 lbs (15.9 kg)

#### **Electrical**

- » 110 220 Volts AC, 50/60 Hz
- » 8MB image memory standard
- » FCC Class A, UL, CUL, & CE approved

#### **Environmental**

- » Operating temperature: 50°F to 95°F (10°C to 35°C)
- » Operation humidity: 20% to 80% non-condensing
- » Storage temperature: -4°F to 158°F (-20°C to 70°C)
- » Storage humidity: 5% to 90% non-condensing
- » Ventilation: Free air

#### **Options**

- » ID/Key security printing feature
- » Magnetic Encoder, 3 track (30 mil cards only, HiCo only)
- » Smart Card Contact Station
- » Smart card MIFARE®/DESFire and HID iClass® encoder/reader
- » Smart Card Contact-ISO 7816 encoder/reader
- » Built-in Ethernet for networking capability
- » Warranty programs

www.zebracard.com



An ISO 9001 registered company ©2005 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trade marks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied Part No. P640i-05/06 by the use thereof.

### **North America**

#### **Zebra Technologies Corporation Card Printer Solutions** 1001 Flynn Road

Camarillo, CA 93012-8706 Telephone: +1 805 579 1800 Fax: +1 805 579 1808 Toll free in US: 800 452 4056 e-mail: cards@zebra.com

### Europe, Middle East, Africa

#### **Zebra Technologies Corporation Card Printer Solutions**

The Valley Centre, Gordon Road High Wycombe Buckinghamshire HP13 6EQ, UK Telephone: +44 870 241 1527 Fax: +44 870 241 0765 e-mail: eurosales@zebra.com

### **Asia Pacific**

#### **Zebra Technologies Corporation Card Printer Solutions**

16 New Industrial Road #05-03 Hudson TechnoCentre Singapore 536204 Telephone: +65 6858 0722 Fax: +65 6885 0836 e-mail: asiasales@zebra.com

### **Latin America**

#### **Zebra Technologies Corporation Card Printer Solutions**

9800 NW 41st Street, Suite 220 Doral, FL 33178 Telephone: +1 305 558 3100 Fax: +1 305 558 8485

e-mail: latinsales@zebra.com